



# Certificate of constancy of performance

0402 - CPR - SC0516-15

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

## **Mechanically operated locks**

as specified in appendix to this certificate,

for use in an appropriate door closing device on fire and/or smoke control doors to fulfil the self-closing requirement of such doors, and thereafter to ensure that the door remains shut

**Product name: ASSA Modul as specified in appendix to this certificate**

produced by or for

**ASSA OEM AB**

**Box 371**

**SE-631 05 Eskilstuna**

**Sweden**

and produced in the manufacturing plants

**Manufacturing site 1, site 2**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in annex ZA of the standard

**EN 12209:2003/AC:2005**

under system 1 for the performances set out in this certificate are applied and that

**the construction products fulfil all the prescribed requirements for these performances.**

This certificate was first issued on 2015-12-22 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared essential characteristics, do not change, and the construction product, and the manufacturing conditions in the plant are not modified significantly, unless suspended or withdrawn by the product certification body.

2015-12-22

**SP Technical Research Institute of Sweden  
Certification, Notified Body No. 0402**

Lennart Månsson  
Certification Manager

Per Adolfsson  
Certification officer

# Certificate of constancy of performance

0402 - CPR - SC0516-15 appendix

## Mechanically operated locks listed below

when used with an appropriate door closing device on fire and/or smoke control doors to fulfil the self-closing requirement of such doors, and thereafter to ensure that the door remains shut.  
Max door weight 200 kg.

### Product name:

ASSA	ASSA	ASSA
565/765	504	6498
560/760	506	1398-28
562/762	509	5761
1560/1760	1520	8768
6585/6785	8560/8760	564
2000	8561/8761	1362-28
7787	1498	13585-28
8765	2565	1361-28

### Performance/Classification:

<b>Self-closing ability</b>	
5.4.2 Closing force	≤ 15 N
5.1.2 Return force of latch bolt	≥ 2.5 N
<b>Durability of self-closing action</b>	
5.3.1 Durability of latch action	200 000 test cycles (load 120 N)
<b>Ability to maintain door in closed position and not contribute to the spread of fire – 5.1.2, 5.5</b>	
Grade 1	